


CW 0222.5 ZH

WARNING CABLE

CEI 20-11 CEI-UNEL 36762 C-4 (U_o = 400 V)

Classe CPR **C**ca-s1b, d1, a1

CU LSZH Pet-sp CU LAP/SP LSZH



A B C D E F

- A INNER CONDUCTOR PLAIN COPPER
- B INSULATION FLAME RETARDANT NON-CORROSIVE
THERMOPLASTIC FREE OF HALOGENS
- C NON-MIGRATING SPIRAL POLYESTER TAPE
- D DRAIN WIRE PLAIN COPPER
- E SHIELD SPIRAL ALUMINIUM + POLYESTER TAPE
COVERAGE 100%
- F SHEATH FLAME RETARDANT NON-CORROSIVE
THERMOPLASTIC FREE OF HALOGENS

- PRINTING **SIVA CAVO ALLARME 2 X 0,50 + 2 X 0,22 CEI-UNEL 36762
C-4 (U_o = 400 V) MADE IN ITALY CE 62 SETT/ANNO
EN 50575:2014 + A1:2016 Cca-s1b, d1, a1**

TEMPERATURE RANGE -40 °C / +80 °C

MECHANICAL DATA

| | CONSTRUCTION | SECTION | SHEATH | WEIGHT KG/KM TOTAL |
|---------------------|--------------------|--------------------------|------------------|-----------------------|
| CW 0222.5 ZH | 2 x (7 x 0,18 mm) | 2 x 0,22 mm ² | ø 4,30 ± 0,20 mm | bianco 9003 |
| | 2 x (16 x 0,18 mm) | 2 x 0,50 mm ² | | |

ELECTRICAL PROPERTIES at 20°C

| | VOLTAGE | | CORES RESISTANCE | | MIN. RESISTANCE INSULATION |
|---------------------|-----------|--------|----------------------|----------------------|-------------------------------|
| | OPERATING | TEST | 0,22 mm ² | 0,50 mm ² | |
| CW 0222.5 ZH | 150 V | 2000 V | 100 Ohm/Km | 42 Ohm/Km | 200 MOhm/Km |

The producer reserves himself to make modification on the item without any notice.