



FABBRICA CAVI - ANTENNE - ACCESSORI TV



M 3... SN

MICROPHONE CABLE TINNED COPPER BRAID

CS

PVC

CS

PVC



A

B

C

D

- A** INNER CONDUCTOR TINNED COPPER
- B** INSULATION POLYVINYL-CHLORIDE
..... COTTON
- C** BRAID TINNED COPPER
- D** SHEATH POLYVINYL-CHLORIDE
- COLOUR BLACK - RAL 9004

TEMPERATURE RANGE -40 °C / +70 °C

MECHANICAL DATA

	INNER CONDUCTOR		SHIELD COVERAGE	SHEATH	WEIGHT KG/KM	
	CONSTRUCTION	SECTION			COPPER	TOTAL
M 3050 SN	3x(16 x 0,20 mm)	3 x 0,50 mm ²	70%	ø 5,20 ± 0,20 mm	21,2	43,4

ELECTRICAL PROPERTIES at 20°C

	CAPACITANCE		CORES RESISTANCE	VOLTAGE	
	CORE TO CORE	CORE TO SHIELD		OPERATING	TEST
M 3050 SN	120 pF/m	250 pF/m	39 Ohm/Km	250 Vca	1200 Vca

The producer reserves himself to make modification on the item without any notice.