




FABBRICA CAVI - ANTENNE - ACCESSORI TV

# RG 059 BU

75 OHM RF COAXIAL CABLE

Class CPR **E<sub>ca</sub>**



## MECHANICAL DATA

<b>A</b>	<b>INNER CONDUCTOR</b>	COPPERWELD	.....	<b>ø 0,58 mm</b>
<b>B</b>	<b>DIELECTRIC</b>	LOW DENSITY POLYETHYLENE	.....	<b>ø 3,70 ± 0,10 mm</b>
<b>C</b>	<b>BRAID</b>	PLAIN COPPER	.....	<b>168 x 0,10 mm</b>
		- COVERAGE	.....	<b>92%</b>
<b>D</b>	<b>SHEATH</b>	NON-CONTAMINATING POLYVINYL-CHLORIDE		<b>ø 6,20 ± 0,10 mm</b>
	- COLOUR	<b>BLACK - RAL 9004</b>		
	- PRINTING	<b>M17/29-RG59 MIL-C-17G RG 59 BU 75 Ohm</b>		
		<b>MADE IN ITALY CE 56 WEEK/YEAR EN 50575:2014 + A1:2016 Eca</b>		

### MINIMUM BENDING RADIUS ( mm )

- **SINGLE** ø EXTERNAL X 5
- **REPEATED** ø EXTERNAL X 10

**TEMPERATURE RANGE** -30 °C / +70 °C

### CABLE WEIGHT ( Kg/Km )

- **COPPER** 14,7
- **PLASTIC** 35,4
- **TOTAL** 50,1

## ELECTRICAL PROPERTIES at 20°C

<b>IMPEDANCE</b>	75 ± 3 Ohm	<b>RESISTANCE</b>	
		- <b>INNER CONDUCT.</b>	166 Ohm/Km
<b>CAPACITANCE</b>	67 pF/m	- <b>BRAID</b>	13 Ohm/Km
<b>VELOCITY RATIO</b>	66%	<b>TENSION</b>	
		- <b>SHEATH</b>	5,0 kV
		- <b>SPARK TESTING</b>	

### ATTENUATIONS dB/100 m.

		<b>dB</b>	<b>W</b>
5	MHz	2,3	
10	MHz	3,1	
50	MHz	7,4	
100	MHz	10,7	
200	MHz	15,7	
400	MHz	22,7	

### MAX. POWER RATING W

		<b>dB</b>	<b>W</b>
500	MHz	25,7	
600	MHz	28,7	
800	MHz	33,6	
1000	MHz	38,0	
1350	MHz	45,6	
1500	MHz	48,5	

		<b>dB</b>	<b>W</b>
1750	MHz	53,5	
2150	MHz	60,9	
2250	MHz	62,1	
2500	MHz	66,8	
2750	MHz	69,6	
3000	MHz	72,7	

### STRUCTURAL RETURN LOSS dB

30 ÷ 300	MHz	>31	1000 ÷ 2000	MHz	>18
300 ÷ 600	MHz	>28	2000 ÷ 3000	MHz	>14
600 ÷ 1000	MHz	>24	..... ÷ .....	MHz	-

### SCREENING EFFECTIVENESS dB

100 ÷ 900	MHz	>57
900 ÷ 2000	MHz	-
2000 ÷ 3000	MHz	-

The producer reserves himself to make modification on the item without any notice.