



FABBRICA CAVI - ANTENNE - ACCESSORI TV

RG 223 TK

DOUBLE SCREENED 50 OHM RF COAXIAL CABLE

Class CPR **E_{ca}**

CA PE CA CA PVC2
 ø 0,90 mm ø 2,95 mm ø 3,50 mm ø 4,00 mm ø 5,40 mm



|| A || B || C || D || E ||

MECHANICAL DATA

A	INNER CONDUCTOR	SILVERED COPPER	ø 0,90 mm
B	DIELECTRIC	LOW DENSITY POLYETHYLENE	ø 2,95 ± 0,10 mm
C	1° BRAID	SILVERED COPPER	112 x 0,13 mm
		- COVERAGE	95%
D	2° BRAID	SILVERED COPPER	112 x 0,13 mm
		- COVERAGE	95%
E	SHEATH	NON-CONTAMINATING POLYVINYL-CHLORIDE	ø 5,40 ± 0,10 mm
	- COLOUR	WHITE - RAL 9003	
	- PRINTING	M17/84-RG223 MIL-C-17F RG 223 U 50 Ohm MADE IN ITALY CE 56 WEEK/YEAR EN 50575:2014 + A1:2016 Eca	

MINIMUM BENDING RADIUS (mm)

- SINGLE ø EXTERNAL X 5
- REPEATED ø EXTERNAL X 10

TEMPERATURE RANGE

-30 °C / +70 °C

CABLE WEIGHT (Kg/Km)

- COPPER 36,8
- PLASTIC 21,4
- TOTAL 58,2

ELECTRICAL PROPERTIES at 20°C

IMPEDANCE 50 ± 3 Ohm

CAPACITANCE 100 pF/m

VELOCITY RATIO 66%

RESISTANCE

- INNER CONDUCT. 28,0 Ohm/Km
- BRAID 8,7 Ohm/Km

TENSION

- SHEATH 3,5 kV
- SPARK TESTING

ATTENUATIONS dB/100 m.

		dB	W
5	MHz	2,6	1131
10	MHz	3,8	800
30	MHz	7,1	462
50	MHz	9,2	358
150	MHz	16,6	207
220	MHz	20,3	171

MAX. POWER RATING W

		dB	W
450	MHz	30,1	119
600	MHz	35,4	103
800	MHz	41,6	89
900	MHz	44,5	84
1000	MHz	47,4	80
1500	MHz	60,5	65

		dB	W
1800	MHz	67,4	60
2000	MHz	72,2	57
2500	MHz	82,6	51
3000	MHz	90,5	46
5200	MHz	126,3	35
5800	MHz	136,7	34

STRUCTURAL RETURN LOSS dB

30 ÷ 450 MHz	>28	2000 ÷ 3000 MHz	>23
450 ÷ 1000 MHz	>25	3000 ÷ 4000 MHz	>22
1000 ÷ 2000 MHz	>24	4000 ÷ 5800 MHz	>21

SCREENING EFFECTIVENESS dB

100 ÷ 900 MHz	>76
900 ÷ 2000 MHz	
2000 ÷ 3000 MHz	

The producer reserves himself to make modification on the item without any notice.