



FABBRICA CAVI - ANTENNE - ACCESSORI TV

ZHD 206 H2C2 - 0,6/1 kV

75 OHM VIDEO SECURITY COAXIAL CABLE

ZHD 206 + 1 TWISTED PAIR 0,22 MM² + 2 x 0,75 MM²

LAYING TOGETHER WITH POWER CABLES MARKING 0,6/1 kV

MAXIMUM VIDEO SIGNAL TRANSMISSION: ANALOGICAL HD - SDI 400 m.
70 m.

CW	PEE	LTA	CS	LSZH	LSZH
ø 0,41 mm	ø 1,95 mm	ø 2,05 mm	ø 2,45 mm	ø 3,60 mm	ø 7,50 mm



MECHANICAL DATA

A	INNER CONDUCTOR	COPPERWELD	ø 0,41 mm
B	DIELECTRIC	FOAM POLYETHYLENE	ø 1,95 ± 0,10 mm
C	SHIELD	ALUMINIUM + POLYESTER + ALUMINIUM TAPE	h. 8 mm
	- COVERAGE		100%
D	BRAID	TINNED COPPER	48 x 0,10 mm
	- COVERAGE		62%
E	SHEATH	FLAME RETARDANT NON-CORROSIVE THERMOPLASTIC FREE OF HALOGENS	ø 3,60 ± 0,10 mm
	- COLOUR	BLUE - RAL 5010	

ELECTRICAL CABLES

		PLAIN COPPER	1 x (2x0,22 mm ²)
		FLAME RETARDANT POLYVINYL-CHLORIDE	1 x (2 x ø 1,20 ± 0,10 mm)
	COLOUR	YELLOW - GREEN TWISTED	
		PLAIN COPPER	2x0,75 mm ²
		FLAME RETARDANT POLYVINYL-CHLORIDE	2 x ø 2,00 ± 0,10 mm
	COLOUR	RED - BLACK	
F	SHEATH	FLAME RETARDANT NON-CORROSIVE THERMOPLASTIC FREE OF HALOGENS	ø 7,50 ± 0,30 mm
	COLOUR	GREY - RAL 7001	

MINIMUM BENDING RADIUS (mm)

- SINGLE	ø EXTERNAL X 5
- REPEATED	ø EXTERNAL X 10

CABLE WEIGHT (Kg/Km)

- COPPER	22,3
- PLASTIC	58,4
- TOTAL	81,5

TAMPERATURE RANGE -40 °C / +80 °C

ELECTRICAL PROPERTIES at 20°C

IMPEDANCE	75 ± 5 Ohm
CAPACITANCE	56 pF/m
VELOCITY RATIO	80%
RESISTANCE - INNER CONDUCT.	320,0 Ohm/Km
- BRAID	41,0 Ohm/Km

ELECTRICAL CABLES

VOLTAGE - OPERATING	250 Vca - 300 Vca
- TEST	1200 Vca - 2000 Vca
CORES RESIST.	82 Ohm/Km - 26 Ohm/Km

ATTENUATIONS dB/100 m.

5 MHz	3,7	100 MHz	15,3	1000 MHz	49,9
10 MHz	4,7	300 MHz	26,1	2150 MHz	74,8
50 MHz	11,0	600 MHz	37,9	3000 MHz	87,5

STRUCTURAL RETURN LOSS dB

30 ÷ 470 MHz	>28	2150 ÷ 3000 MHz	>15
470 ÷ 860 MHz	>23 ÷	MHz -
860 ÷ 2150 MHz	>18 ÷	MHz -

SCREENING EFFECTIVENESS dB

100 ÷ 900 MHz	>75
900 ÷ 2000 MHz	-
2000 ÷ 3000 MHz	-

The producer reserves himself to make modification on the item without any notice.

SI.VA S.R.L. Via Vittorio Veneto 63 24040 Bonate Sotto (Bergamo) Italia

Tel. 0039 035 991085 / 86 Fax 0039 035 992128 Home page: <http://www.sivacavi.it> E-mail: siva@sivacavi.it