



FABBRICA CAVI - ANTENNE - ACCESSORI TV



CW7

WARNING CABLE
CEI-UNEL 36762 C-4 (U_o = 400 V)

Class CPR **E_{ca}**

CU PLSF Pet-sp CU LAP/SP PLSF



| | A | B | C | D | E | F |
|----------|-----------------|-------|--|---|---|---|
| A | INNER CONDUCTOR | | PLAIN COPPER | | | |
| B | INSULATION | | LOW SMOKE AND FUME POLYVINYL-CHLORIDE | | | |
| C | NON-MIGRATING | | SPIRAL POLYESTER TAPE | | | |
| D | DRAIN WIRE | | PLAIN COPPER | | | |
| E | SHIELD | | SPIRAL ALUMINIUM + POLYESTER TAPE COVERAGE 100% | | | |
| F | SHEATH | | LOW SMOKE AND FUME POLYVINYL-CHLORIDE | | | |

- PRINTING

**SIVA CAVO ALLARME SECTION MM² CEI-UNEL 36762
C-4 (U_o = 400 V) MADE IN ITALY CE 62 SETT/ANNO
EN 50575:2014 + A1:2016 E_{ca}**

TEMPERATURE RANGE -25°C / +80°C

MECHANICAL DATA

| | CONSTRUCTION | SECTION | SHEATH | | WEIGHT KG/KM TOTAL |
|------------------|--------------------|---------------------------|------------------|------------------|-----------------------|
| CW 0222.7 | 2 x (7 x 0,18 mm) | 2 x 0,22 mm ² | ø 4,80 ± 0,20 mm | White - RAL 9003 | 35,0 |
| | 2 x (24 x 0,18 mm) | 2 x 0,75 mm ² | | | |
| CW 0422.7 | 4 x (7 x 0,18 mm) | 4 x 0,22 mm ² | ø 5,50 ± 0,20 mm | White - RAL 9003 | 42,1 |
| | 2 x (24 x 0,18 mm) | 2 x 0,75 mm ² | | | |
| CW 0622.7 | 6 x (7 x 0,18 mm) | 6 x 0,22 mm ² | ø 6,00 ± 0,20 mm | White - RAL 9003 | 48,8 |
| | 2 x (24 x 0,18 mm) | 2 x 0,75 mm ² | | | |
| CW 0822.7 | 8 x (7 x 0,18 mm) | 8 x 0,22 mm ² | ø 6,60 ± 0,20 mm | White - RAL 9003 | 55,8 |
| | 2 x (24 x 0,18 mm) | 2 x 0,75 mm ² | | | |
| CW 1022.7 | 10 x (7 x 0,18 mm) | 10 x 0,22 mm ² | ø 7,40 ± 0,20 mm | White - RAL 9003 | 63,1 |
| | 2 x (24 x 0,18 mm) | 2 x 0,75 mm ² | | | |
| CW 1222.7 | 12 x (7 x 0,18 mm) | 12 x 0,22 mm ² | ø 8,00 ± 0,20 mm | White - RAL 9003 | 69,8 |
| | 2 x (24 x 0,18 mm) | 2 x 0,75 mm ² | | | |
| CW 1422.7 | 14 x (7 x 0,18 mm) | 14 x 0,22 mm ² | ø 8,80 ± 0,20 mm | White - RAL 9003 | 75,5 |
| | 2 x (24 x 0,18 mm) | 2 x 0,75 mm ² | | | |

ELECTRICAL PROPERTIES at 20°C

| | VOLTAGE | | CORES RESISTANCE | | MIN. RESISTANCE INSULATION |
|------------------|-----------|--------|----------------------|----------------------|-------------------------------|
| | OPERATING | TEST | 0,22 mm ² | 0,50 mm ² | |
| CW7 | 150 V | 2000 V | 100 Ohm/Km | 29 Ohm/Km | 200 MOhm/Km |

The producer reserves himself to make modification on the item without any notice.