



FABBRICA CAVI - ANTENNE - ACCESSORI TV



AR 58 SHF1



DOUBLE SCREENED 50 OHM RF COAXIAL CABLE
MANUFACTURED IN COMPLIANCE WITH MIL-C-17F STANDARDS
IN ACCORDANCE TO : IEC 60092-359 IEC 60332-1-2 IEC 60332-3-22/24
IEC 60754-1 IEC 60754-2 IEC 60811-3-1 IEC 61034-2

CS **PE** **LTA** **CS** **LSZH** **FE-ZN** **LSZH**
19 x 0,18 mm **ø 2,95 mm** **ø 3,05 mm** **ø 3,60 mm** **ø 5,00 mm** **ø 6,00 mm** **ø 8,00 mm**



A **B** **C** **D** **E** **F** **G**

MECHANICAL DATA

A	INNER CONDUCTOR	TINNED COPPER	19 x 0,18 mm
B	DIELECTRIC	LOW DENSITY POLYETHYLENE	ø 2,95 ± 0,10 mm
C	SHIELD	ALUMINIUM + POLYESTER + ALUMINIUM TAPE		h. 15 mm
	- COVERAGE		100%
D	BRAID	TINNED COPPER	112 x 0,13 mm
	- COVERAGE		93%
E	SHEATH	FLAME RETARDANT NON-CORROSIVE THERMOPLASTIC FREE OF HALOGENS		ø 5,00 ± 0,20 mm
	- COLOUR	BLACK - RAL 9004		
G	ARM	ZINC-PLATED STEEL	96 x 0,24 mm
	- COVERAGE		93%
H	SHEATH	FLAME RETARDANT NON-CORROSIVE THERMOPLASTIC FREE OF HALOGENS		ø 8,00 ± 0,20 mm
	- COLOUR	BLACK - RAL 9004		
	- PRINTING	## METER ## NEK KABEL SETT/ANNO RG 58 CU MARINE SHF1 ARMOURED 50 OHM IEC 60332-3-22/24 CAT.A DNV SC..... CE		

MINIMUM BENDING RADIUS (mm)		CABLE WEIGHT (Kg/Km)
- SINGLE	ø EXTERNAL X 5	- COPPER 18,7
- REPEATED	ø EXTERNAL X 10	- PLASTIC 55,4
TEMPERATURE RANGE	-40 °C / +80 °C	- TOTAL 113,0

ELECTRICAL PROPERTIES at 20°C

IMPEDANCE	50 ± 2 Ohm	RESISTANCE	
CAPACITANCE	100 pF/m	- INNER CONDUCT.	36,5 Ohm/Km
VELOCITY RATIO	66%	- BRAID	12,0 Ohm/Km
		TENSION	
		- SHEATH	3,5 kV
		SPARK TESTING	

ATTENUATIONS dB/100 m.

		dB	W
5	MHz	3,0	
10	MHz	4,1	
30	MHz	7,5	
50	MHz	9,7	
150	MHz	16,4	
220	MHz	20,1	

MAX. POWER RATING W

		dB	W
450	MHz	30,0	
600	MHz	35,4	
800	MHz	41,6	
900	MHz	44,5	
1000	MHz	47,5	
1500	MHz	60,9	

		dB	W
1800	MHz	68,1	
2000	MHz	73,3	
2500	MHz	85,1	
3000	MHz	91,3	
5200	MHz	-	
5800	MHz	-	

STRUCTURAL RETURN LOSS dB

30 ÷ 450 MHz	>27	2000 ÷ 3000 MHz	>18
450 ÷ 1000 MHz	>25	3000 ÷ 4000 MHz	-
1000 ÷ 2000 MHz	>20	4000 ÷ 5800 MHz	-

SCREENING EFFECTIVENESS dB

100 ÷ 900 MHz	>95
900 ÷ 2000 MHz	>90
2000 ÷ 3000 MHz	>80

The producer reserves himself to make modification on the item without any notice.