



FABBRICA CAVI - ANTENNE - ACCESSORI TV



CW 0822

WARNING CABLE
CEI-UNEL 36762 C-4 (U_o = 400 V)

Class CPR **E_{ca}**

CU PLSF Pet-sp CU LAP/SP PLSF



|| A || B || C || D || E || F ||

- A INNER CONDUCTOR PLAIN COPPER
- B INSULATION LOW SMOKE AND FUME POLYVINYL-CHLORIDE
- C NON-MIGRATING SPIRAL POLYESTER TAPE
- D DRAIN WIRE PLAIN COPPER
- E SHIELD SPIRAL ALUMINIUM + POLYESTER TAPE
COVERAGE 100%
- F SHEATH LOW SMOKE AND FUME POLYVINYL-CHLORIDE

- PRINTING

**SIVA CAVO ALLARME 8 X 0,22 CEI-UNEL 36762
C-4 (U_o = 400 V) MADE IN ITALY CE 62 SETT/ANNO
EN 50575:2014 + A1:2016 Eca**

TEMPERATURE RANGE -25°C / +80°C

MECHANICAL DATA

| CONSTRUCTION | SECTION | SHEATH | WEIGHT KG/KM TOTAL |
|--------------|---------|--------|-----------------------|
|--------------|---------|--------|-----------------------|

| | | | | | |
|----------------|-------------------|--------------------------|------------------|-------------|------|
| CW 0822 | 8 x (7 x 0,15 mm) | 8 x 0,22 mm ² | ø 4,70 ± 0,20 mm | bianco 9003 | 30,4 |
|----------------|-------------------|--------------------------|------------------|-------------|------|

ELECTRICAL PROPERTIES at 20°C

| VOLTAGE | | CORES RESISTANCE | MIN. RESISTANCE INSULATION |
|-----------|------|---------------------|-------------------------------|
| OPERATING | TEST | | |

| | | | | |
|----------------|-------|--------|------------|-------------|
| CW 0822 | 150 V | 2000 V | 140 Ohm/Km | 200 MOhm/Km |
|----------------|-------|--------|------------|-------------|

The producer reserves himself to make modification on the item without any notice.